

PUV CLASS I

A Toyota Group Company



LIGHT AND CONVENIENT TRANSPORT SOLUTION









LIGHT AND CONVENIENT TRANSPORT SOLUTION



Ample Air Circulation



Two Options for Window:

- Clear Tarp Cover and
- Sliding Tempered Window



High Quality Body Construction




High Visibility Tail Light



SPECIFICATIONS

RANGE / SERIES	HINO PUV
MODEL NAME	PUV CLASS 1
MODEL CODE	HINO 415J
SEATING CAPACITY	14
DRIVE SYSTEM	4 x 2 (4W)
BODY	
Туре	Single Desk Skeleton Type Body
Construction	Combination of G.A, RHS and Bended Sheet Metal
Rear	G.A Sheet 0.8mm
Flooring	MSP 2.0 mm Structure w/ Corrugated G.A. 1.0mm Floor Panels
Side and Door Panel	G.A Sheet 0.8mm with G.A Sheet 1.0 Stiffener, & RHS #16 40 x 50
Body Treatment	Multi-Stage Poly-Urethane Paint, Rust Proofing and Under-Coating
Seats	Perimeter Seating with Foam Cushion and Backrest
ENGINE	
Model	1GD-FTV
Max. Output (PS) ISO JIS	144
Max. Torque (N.m) ISO JIS	300
Emission Standard	Euro 4
Max. Engine Speed (rpm)	4,400
Туре	Diesel Turbocharged and Intercooled, 4-cycle, Inline, 4-cylinder, Double-Overhead Valve, Water-Cooled
Combustion System	Direct Injection Type
Fuel Injection System	Electronic Control Common Rail Type
Displacement (L)	2.755
Fuel Tank Capacity (L)	80
TRANSMISSION	
Туре	5-Speed M/T with Overdrive
PERFORMANCE	
Max. Speed (kph)	130
Gradeability (%)	43.0
BRAKES	
Service (Type)	Dual-Circuit, Hydraulic, Vacuum Assist
(Features)	N/A
Parking	Mechanical, Internal Expanding, Acting on Transmission Output Shaft
WHEELS & TIRES	
Tire Size	195/75R15
SUSPENSIONS	
Front	Double Wishbone, Independent Torsion Bar Springs with Double Acting Shock Absorbers and Stabilizer
Rear	Semi-Elliptic Main and Auxiliary Leaf Springs and Rubber Rebound Bumpers with Double Acting Shock Absorbers
DIMENSIONS & WEIGHTS	
Wheelbase (mm)	2,545
Overall Length (mm)	4,500
Overall Width (mm)	1,710
Overall Height (mm)	2,500
Gross Vehicle Weight (Kg)	3,800
Front Overhang (mm)	955
Rear Overhang (mm)	994





Spacious Interior for Passsengers



Premium Leatherette Upholstery




Laminate Interior Ceiling Finish



Alternate Steps for Easy Loading



4,494mm



Class 1 Seating Layout









